



P8

Inspection Document
EN 10204
Prüfbescheinigung

HILTI (CHINA) LTD.
Yongping Road, South,
Zhanjiang, Guangdong, PRC

Document No. *Dokument Nr.*

P8_2.2_160

Item-Nr.	Product designation	Customer ref. -Nr.	Batch-Nr.	Quantity
<i>Sach-Nr.</i>	<i>Produktbezeichnung</i>	<i>Kunden Ref. Nr.</i>	<i>Charge/Los Nr.</i>	<i>Menge</i>
Code art.	Référence produit	No. ref. de client	Commande No.	Quantité
409561	Anchor rod HIT-V-F M16x200			

Item designation	Anchor rod	Rod	Nut	Washer		
<i>Sachbezeichnung</i>	HIT-V-F	螺杆	螺母	垫片		
<i>Reference composant</i>	M16x200					

Inspection values/Prüfergebnisse

Chemical composition		set value	actual value	set value	actual value	set value	actual value	set value	actual value	set value	actual value
<i>Chem. Zusammensetzung</i>											
C %		0.00-0.55	0.32	0.00-0.58	0.15						
Si %											
Mn %				min. 0.30	0.43						
P %		0.000-0.050	0.025	0.000-0.060	0.009						
S %		0.000-0.060	0.019	0.000-0.150	0.001						
Cr %											
Mo %											
Ni %											
Cu %											
B %											
Al %											
N %											
Pb %											
Mech. properties											
<i>Mechanische Eigensch. / Mecan. prop.</i>											
N											
V											
F _p				126	126						
HV						140-250	150-182				
HRC											
A		min. 10	13-17								
Z											
R _{p0.2}		min. 420	433-469								
R _m		min. 520	573-659								
Layer thickness/Schichtdicke											
<i>Epaisseur de couche extérieure</i>											
d (Zn)		min. 40	53-75	min. 40	51-63	min. 40	47-68				
N	kN	Tension load / Bruchlast Zug / charge de tension				Z	%	Reduction of area / Einschnürung / contraction			
V	kN	Shear load / Querlast / charge de cisaillement				R _{p0.2}	N/mm ²	Yield strength / Streckgrenze / limite d'élasticité			
F _p	N	Proof load / Prüfkraft / charge limite				R _m	N/mm ²	Ultimate tensile strength / Zugfestigkeit / résistance à la			
HV	-	Vickers hardness / Härte Vickers / dureté Vickers				d (Zn)	µm	Mean zinc thickness / mittlere Schicht-dicke Zn / epaisseur			
A	%	Elongation after fracture / Bruch-dehnung / elongation après fracture									