

DECLARATION OF PERFORMANCE

No. 2873-CPR-201-46

1. Unique identification code of the product type:

Undercut anchor HSU-R

2. Intended use/es:

Product	Intended use
Metal anchors for use in concrete	For use in systems, such as façade systems, for fixing or supporting elements which contribute to the stability of the systems

3. Manufacturer:

Hilti Corporation Business Unit Anchors, 9494 Schaan, Principality of Liechtenstein

4. System/s of AVCP:

System 2+

5. European Assessment Document

EAD 330030-00-0601

European Technical Assessment:

ETA-16/0784 (13.03.2019)

Technical Assessment Body:

DIBt – Deutsches Institut für Bautechnik

Notified body/ies:

2873 - IFSW Darmstadt

6. Declared performance/s:**Mechanical resistance and stability (BWR 1)**

Essential characteristic	Performance
Durability	See Annex Corrosion Resistance Class III acc. to EN 1993.1-4:2015
Edge distances and spacing	See Annex B3 & C1
Characteristic resistance for static and quasi static loads	See Annex C1

Safety in case of fire (BWR 2)

Essential characteristic	Performance
Reaction to fire	Anchorage satisfy requirements for class A1
Resistance to fire	No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above

Signed for and on behalf of the manufacturer by:

Edward-Luis Przybyłowicz

Business Unit Head

Business Unit Anchor

Gunnar Wald

Head of Quality

Business Unit Anchor