



DECLARATION OF PERFORMANCE

No. 2873-CPR-201-38

1. Unique identification code of the product type:

Injection system for use in concrete HIT-HY 150 MAX

2. Intended use/es:

Product	Intended use
	For fixing and/or supporting to concrete, structural elements (which contributes to the stability of the works) or heavy units.

3. Manufacturer:

Hilti Corporation Business Unit Anchors, 9494 Schaan, Principality of Liechtenstein

4. System/s of AVCP:	System 1
5. European Assessment Document	EAD 330499-00-0601 (Edition 07-2017) (Edition (07-2017))
European Technical Assessment:	ETA-08/0352 (25.06.2018)
Technical Assessment Body:	DIBt – Deutsches Institut für Bautechnik
Notified body/ies:	2873 - IFSW Darmstadt

6. Declared performance/s:

Mechanical resistance and stability (BWR 1)

Essential characteristic	Performance
Characteristic resistance for static and quasi static loads, displacements	See Annex C1-C15

Safety in case of fire (BWR 2)

Essential characteristic	Performance
Reaction to fire	Anchorages satisfy requirements for class A1
Resistance to fire	No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsability of the manufacturer identified above

Signed for and on behalf of the manufacturer by:

Edward-Luis Przybylowicz Business Unit Head Business Unit Anchor

Gunnar Wald Head of Quality Business Unit Anchor







DECLARATION OF PERFORMANCE

No. 2873-CPR-201-39

1. Unique identification code of the product type:

Injection system for rebar connection HIT-HY 150 MAX

2. Intended use/es:

Product	Intended use
	For fixing and/or supporting to concrete, structural elements (which contributes to the stability of the works) or heavy units.

3. Manufacturer:

Hilti Corporation Business Unit Anchors, 9494 Schaan, Principality of Liechtenstein

System 1
EAD 330087-00-0601 (07-2015) (Edition (07-2015))
ETA-08/0202 (25.06.2018)
CSTB – Centre Scientifique et Technique du Batiment
2873 - IFSW Darmstadt

6. Declared performance/s:

Mechanical resistance and stability (BWR 1)

Essential characteristic	Performance
Characteristic resistance for static and quasi static loads	See Annex C1

Safety in case of fire (BWR 2)

Essential characteristic	Performance
Reaction to fire	Anchorages satisfy requirements for class A1
Resistance to fire	No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsability of the manufacturer identified above

Signed for and on behalf of the manufacturer by:

Edward-Luis Przybylowicz Business Unit Head Business Unit Anchor

Gunnar Wald Head of Quality Business Unit Anchor

