

EN

DECLARATION OF PERFORMANCE

according to the Construction Products Regulation in the UK (UK CPR)

Hilti Drywall Fastening Screws S-WD No. Hilti-SF-DoP-024-GB

1. Unique identification code of the product-type: Hilti Drywall Fastening Screws S-WD

**2.** Type, batch or serial number or any other element allowing identification of the construction product: Type and Lot-Number displayed on the packaging

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Generic type and use	Fastening screws for gypsum boards, fastening of wood to steel structures	
Product size covered	3.8, 3.9, 4.2, 4.8, 5.5, 6.3 mm thread diameter	
Base and fastened material	Gypsum boards or wood substructure to steel structures of steel grade ≥ S235	
Base material condition	Metal profile total thickness   S-WD11 Ø 3.8mm $1.00 \le t \le 1.50$ mm   S-WD11 Ø 3.9mm $1.00 \le t \le 1.50$ mm   S-WD11 Ø 4.2mm $2.10 \le t \le 3.50$ mm   S-WD13 Ø 4.8mm $2.10 \le t \le 4.50$ mm   S-WD13 Ø 5.5mm $2.10 \le t \le 5.50$ mm   S-WD13 Ø 6.3mm $2.60 \le t \le 6.00$ mm   S-WD15 Ø 5.5mm $4.60 \le t \le 12.00$ mm	
Fastener head type	Countersunk	
Fastener thread type	Fine single thread	

**4.** Name, registered trade name or registered trade mark and contact address of the manufacturer: Hilti AG, Business Unit Screw Fastening, 9494 Schaan, Fürstentum Liechtenstein

5. Where applicable, name and contact address of the authorised representative: n.a.

**6.** System or systems of assessment and verification of constancy of performance of the construction product: System 4

**7.** In case of the declaration of performance concerning a construction product covered by a harmonized standard: No third party tasks according to BS EN 14566:2008 required

8. In case of the declaration of performance concerning a construction product for which a United Kingdom Technical Assessment has been issued: n.a.

9. Declared performance:

Essential characteristics	Declared performance	Harmonized Technical Specification
Flexural strength	Pass	BS EN 14566:2008
Reaction to fire	Class A1, no contribution to fire	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Rafael Garcia Head of Business Unit Direct Fastening

Hilti AG, Schaan, 01.01.2023

1/1

Pierre Hohmeier Head of Quality Screw Fastening